

Product Specification

ADRF-2PLX-LPIM Series



Electrical Specification

	ADRF-2PLX-700F-LPIM	ADRF-2PLX-850-LPIM	ADRF-2PLX-1900-LPIM	ADRF-2PLX-2100-LPIM
Frequency Range	RX: 698-716 MHz, 776-787 MHz TX: 728-757 MHz	RX: 824-849 MHz TX: 869-894 MHz	RX: 1850-1915 MHz TX: 1930-1995 MHz	RX: 1710-1755 MHz TX: 2110-2155 MHz
Insertion Loss	RX: 2.7 dB (Max) TX: 2.2 dB (Max)	1.5 dB (Max)	2.0 dB (Max)	1.5 dB (Max)
Passband Ripple	RX: 1.4 dB (Max) TX: 1.2 dB (Max)	1.0 dB (Max)	1.8 dB (Max)	0.2 dB (Max)
VSWR	≤ 1.22 : 1			
Isolation	RX: 80 dB (Min) TX: 70 dB (Min)	70 dB (Min)	90 dB (Min)	80 dB (Min)
Power Rating (Average)	100 W			
Passive Intermodulation	> 153 dBc @ 2 tone x 43 dBm			

General Specification

	ADRF-2PLX-700F-LPIM	ADRF-2PLX-850-LPIM	ADRF-2PLX-1900-LPIM	ADRF-2PLX-2100-LPIM
Dimension (W x H x D)	3.32 x 6.59 x 3.24 in	4.76 x 4.84 x 2.55 in	3.34 x 6.81 x 2.65 in	2.99 x 6.37 x 1.77 in
Weight	3.96 lbs	3.97 lbs	3.08 lbs	2.2 lbs
Operating Temperature	14° – 140° F			
Weather Resistance	IP65 / NEMA4	IP65 / NEMA4	IP67 / NEMA4X	IP65 / NEMA4

Specifications are subject to change without notice. ©2014 Advanced RF Technologies, Inc.